



Dispensing Disc Patterns

Canister Sizes

# Take control. Save up to 90% in transportation and warehouse costs.

# **Systems, Service and Savings**

Huhtamaki Systems Machinery and components allow in-plant forming of your containers on-demand. Quikspread sidewalls are printed then shipped flat to reduce transportation costs and warehousing space. Assemble in your plant with Huhtamaki Systems equipment and components. Fill only what is currently needed or place in inventory to control production requirements and reduce product waste. Huhtamaki Systems, the packaging approach that makes all the difference!

Huhtamaki Systems formers are built in the USA by equipment engineers who understand packaging. These machines are designed with small footprints, minimum utility requirements, easy change over of canister sizes and are simple to operate. Our Systems approach is designed to deliver maximum value and service.

# FM-1400 Automated Quikspread® Forming Machine



Straight-walled with heat sealed flat bottom dispensing end. Variable speeds from 50-75 containers per minute.

**Length:** 7ft. 5in. (2260.6mm) **Width:** 5ft. 4in. (1625.6mm)

**Height:** 7ft. 6in. (2286mm) w/guards in operating position 9ft. 0in. (2743.2mm) w/guards in service position

Conveyor Height: 37in. - 39in. (939.8mm - 990.6mm) Adjustable

Weight: 8,000lbs. (3,629kg)

Electrical: 240 Volts A.C., 3-phase, 50/60Hz, 80amps

Pneumatic: 80-90psi, 100scfm, measured at the machine

### **UL-4400 Automated Quikspread® Plug Inserter/Sealer/Crimper**



Cycles on demand up to 70 containers per minute.

 Length:
 12ft. 10in. (3911.6mm)

 Width:
 4ft. 4in. (1320.8mm)

 Height:
 6ft. 5in. (1955.8mm)

 Weight:
 3,500lbs. (1591kg)

Electrical: 240 Volts A.C., 3-phase, 50/60Hz, 60amps

Pneumatic: 80-100psi, 60scfm, measured at the machine

# **CF-3200 Automated Plug Unscrambler/Feeder (feeds UL)**



 Variable, up to 180 plugs per minute.

 Length:
 56in. (1422.4mm)

 Width:
 61in. (1549.4mm)

 Height:
 77in. (1955.8mm)

 Hopper Height:
 42in. (1066.8mm)

 Weight:
 780lbs. (354kg)

Electrical: 240 Volts, 50/60Hz, 10amps

Pneumatic: 50psi, 5scfm

# FM-1300 Quikspread® Semi-Automated Container Forming Machine



Straight-walled with heat sealed flat bottom dispensing end. 5-8 containers per minute, operator dependent.

 Length:
 53in. (1346.2mm)

 Width:
 49in. (1244.6mm)

 Height:
 69in. (1752.6mm)

 Weight:
 1,500lbs. (680.4kg)

Electrical: 240 Volts, 3-phase, 50/60Hz, 18amps

Pneumatic: 70-100psi, 35scfm

# **UL-4300 Quikspread® Semi-Automated Plug Inserter, Sealer and Crimping Machine**



5-8 containers per minute, operator dependent.

 Length:
 36in. (914.4mm)

 Width:
 24in. (609.6mm)

 Height:
 56in. (1422.4mm)

 Conveyor Height:
 39in. (990.6mm)

 Weight:
 200lbs. (90.7kg)

Electrical: 240 Volts, 1-phase, 50/60Hz, 5amps

Pneumatic: 70psi, 10scfm